



YG4430N



Switch with passive infrared ray movement sensor, suitable for all types of load including LED lamps - 3 wires – variable-threshold twilight circuit with possibility of exclusion – timing circuit to delay switching off adjustable from 5 seconds to 10 minutes - 230 V~ power supply - Standby consumption < 0,015W. Master/Slave function available (10 slaves max. for 1 master) Detection field 170°. Detection range 8m. Light level threshold setting from 5 to 1275 lux. 4 levels of sensitivity setting. Accepted power by lamp type : LEDs, CFLs : 0 to 500W LED, Halogens, incandescent : 0 to 2000W, LEDs, CFLs, Halogen, fluo tube with ferromagnetic or electronic transformer: 0 to 1000VA. - 2 modules - stone

Technical features

Brand	BTicino
Rated voltage	230Vac
Rated power (W)	2000W
Modules	2
Series	Light Now

Technical documentation

? Instruction Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.