





CE4DF3MTCL1

IME

Conto D4-Pd -Energy meter, active (cl.1) and reactive (cl.2) Connection: direct - Network: three-phase 4-wires unbalanced -Dimension: 4 DIN modules - Output: M-Bus - Current: 63A -Voltage: 230-400V (phase-phase) - Aux: self-supplied

Technical features

Brand **IME** Rated voltage 230-400Vac **Auxiliary** Autoalimentato / Self-supplied Frequency 50-60Hz Input current 63A 4 Modules Protection class IP20 Accuracy class 1/2Doppia tariffa o impulsi / Double tarif or pulse Input M-bus Output Trifase / three-phase Plant type insertion Diretta / Direct Series

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8032826514135

Technical documentation

? DWG, DXG and STP drawings	? M-BUS protocol
? MODBUS protocol	? Installation manual
? Technical Data Sheet	? Instruction Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.



GENERAL CATALOGUE

Complete with





