CE4TBDTMIDUTF

IME

Conto D4-Pt MID - Energy meter, active MID (cl.B) and reactive (cl.2) Connection: via CT (5A) - UTF DC15 certification - Network: three-phase 4-wires unbalanced - Dimension: 4 DIN modules - Output: RS485 - Input (from CT) : 1A-5A - Voltage: 3x230/400V - Aux: self-supplied

Technical features

Brand	IME
Rated voltage	230-400Vac
Auxiliary	Autoalimentato / Self-supplied
Frequency	50-60Hz
Input current	1-5A
Modules	4
Protection class	IP20
Accuracy class	B
Input	Doppia tariffa o impulsi / Double tarif or pulse
Output	RS485 Modbus
Plant type	Trifase / three-phase
insertion	TA/TV / CT/VT
Series	

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8032826515651

Technical documentation

? MODBUS protocol

? M-BUS protocol

Complete with

CE4TBDTMID
Conto D4-Pt MID - Energy meter, active M...

Source page: *https://catalogue.bticino.com/product/solution-for-measurement-and-supervision-ime/conto-energy-static-meters/mid-modular-static-meters/conto-d4-pt-mid-connection-via-ct/IMS-CE4TBDTMIDUTF-EN*