MFD4411

IME

Nemo D4-Le - Multifunction for application in LV with active energy count (cl.0.5)/reactive (cl.1) on 4 quadrants - Network: single-phase or three-phase 3/4-wires unbalanced - Display: LCD backlit - Dimension: 4 DIN modules - Output: pulse S0 / 1 alarm contact - Input: 80÷500Vac - Auxiliary supply: 80÷265Vac or 100÷300Vdc

Technical features

Brand	IME
Auxiliary	80-265Vac - 100-300Vdc
Input current	1-5A
Modules	4
Protection class	IP20
Accuracy class	0.5/1
Input	80-500Vac (3-PH) 50-290Vac (1-PH)
Output	impulsi / pulse
Plant type	Trifase / three-phase + monofase / single-phase
insertion	TA /CT
Series	

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8032826046940

Technical documentation

? Technical sheet	? Firmware per HW 2.XX
? Firmware for HW 3.XX	? User manual
? Protocol	? Protocol

Complete with

MF96E06
Nemo 96Hde-
Multifunction for
applicatio...

MF96411
Nemo 96HDLe -
Multifunction for applicat...

MF72411
Nemo 72-Le -
Multifunction for
applicati...