



# MFD4E06

**IME**

Nemo D4-e - Multifunction for application in LV with active energy count (cl.1) and reactive (cl.1) on 4 quadrants - Network: single-phase or three-phase 3/4-wires unbalanced - Display: LCD backlit - Dimension: 4 DIN modules - Output: pulse S0 + RS485 Modbus RTU - Input: 80÷500Vac (50÷290Vac for single-phase)- Auxiliary supply: 230Vac

## Technical features

Brand	IME
Auxiliary	230Vac
Input current	5A
Modules	4
Protection class	IP20
Accuracy class	1/1
Input	80-690Vac (3-PH) 50-290Vac (1-PH)
Output	impulsi / pulse + RS485 Modbus
Plant type	Trifase / three-phase + monofase / single-phase
insertion	TA /CT
Series	

## Technical documentation

- ? Technical Data Sheet
- ? Protocol
- ? Manual

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.