



002634

KNX/SCS gateway. It gives the possibility of interfacing SCS products to the KNX bus (for the list of compatible product see the "KNX automation system" guide). The products connected are detected and configured by the ETS as if they were native KNX products. The reference consists of two products, gateway, and SCS power supply. Connection to the KNX bus using the red-black KNX connector, and to the SCS bus using the RJ45 connector. Power supply unit: 100/240 Vac 50/60 Hz, external; gateway power supply: 27 Vdc, external. Fitting on DIN rail: 2 DIN modules for power supply and 2 DIN modules for the controller.

## Technical features

Brand	Legrand
Rated voltage	29 V.d.c.
Modules	2 DIN
Series	

## Technical documentation

? DWG drawing

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.