

# 002635

Image not found



KNX/DALI Gateway for the control of DALI ECG (Electronic control gear), with one output with a maximum load of 64 ECG. It gives the possibility of managing the ECGs in different modes: all in the same way, in groups, individually; or to program up to 16 different lighting scenarios. The gateway also gives the possibility of receiving return information from the system (ECG fault, lamp fault...). Bus connection using a red-black KNX connector. Supply voltage 110 - 240 V 50-60 Hz, and additional power supply from KNX bus. Fitting on DIN rail. Size: 6 DIN modules.

## Technical features

Rated voltage	240Vac
Modules	6 DIN
Series	

## Technical documentation

? DWG drawing

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.