

GENERAL CATALOGUE



002655 Ellegrand

KNX contact interface with 8 independent channels. It can be used for monitoring different devices, like probes, alarms, etc... Main functions: Recording of the switching of status (open/closed), and of the status changes (opening/closing), of the different contacts - Monitoring of the switching status, and of the operating status of the contacts (status of connected devices, alarms...) - Recording of the switching status of the contacts and count of the number of switches, and comparison with preset reference thresholds KNX bus connection using a red-black KNX connector. Supply voltage 100/240 V ac 50/60 Hz. Fitting on DIN rail. Size: 6 DIN modules.

Technical features

Brand	Legrand
Rated voltage	29 Vd.c.
Modules	6 DIN

Series

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.