
X







002663

KNX/DALI interface with 8 independent channels, each capable of managing up to 8 ballasts. Main functions: Switching, dimmer and forwarding of a dimmer level value - Configuration of ON / OFF switching times, dimmer from 0 to 100 % and from 100 to 0% - Configuration of the minimum / maximum dimmer level - Configuration of 8 bit scenarios for each channel, with the possibility to assign up to 16 scenarios to one channel - Configuration of the objects for the return of the status relating to lamp switching/ dimmer/fault, and DALI status Bus connection using a red-black KNX connector. Supply voltage 110 - 240 V 50-60 Hz. Fitting on DIN rail. Size: 4 DIN modules.

Technical features

Rated voltage	110-240Vac
Modules	4 DIN
Series	

Technical documentation

? ETS Project File

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The optimizance are be proved by Certificates is sused by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.