

002676



All-in-one multi-application controller equipped with 16 outputs capable of performing multiple functions including: - ON-OFF lights control or dimming - Control of shutters and curtains - Control of controlled sockets - control of fan coils with 2 and 3 point valves Suitable for managing resistive, capacitive, inductive loads and fluorescent lamps with different functions. Independent input channels operating as a universal interface with the following functions: switch / button input, dimmer control, shutter / blind control, value sending, scene control, counter for counting pulses. Each output can be controlled via traditional electromechanical devices or KNX devices Configuration via ETS sw. Bus connection via red-black KNX connector. Power supply SELV 29V d.c from KNX bus (< 10mA). DIN rail installation. Dimensions: 10 DIN modules.

Technical features

Brand	Legrand
Reference Standard	EN 50090 - EN 13321-1 e ISO/IEC 14543-3
Rated voltage	29 Vd.c.
Input current	10 mA
Modules	10 DIN
Protection class	IP 20
Plant type	KNX
Series	KNX

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	3414972052344

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.