


# 002682



KNX actuator controller with 12 independent channels each of maximum load 16 A, suitable for control of light loads or power sockets. Main functions: - Selection of normal or time switch operating mode - ON / OFF switching with delay - Operating mode PWM - Configuration of 2 logic functions - Configuration 5 scenarios - Configuration of the contact behavior of the crossing of a threshold (upper / lower) - Configuration of the status of the return contacts Main Power or BUS KNX - Configuration of the value of the items to the main power returns or the KNX BUS Connection to the bus via red-black KNX connector. Supply voltage SELV 29 Vd.c from KNX bus. DIN rail mounting, dimensions: 12 DIN modules.

## Technical features

Brand	Legrand
Rated voltage	29Vdc
Modules	12

Series

### Technical documentation

? ETS Project File	? DWG drawing
? DWG drawing	? Instruction Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.