

GENERAL CATALOGUE



002686

Controller KNX universal dimmer 2-channel maximum load 500 VA for control of incandescent lamps, halogen lamps and halogen lamps with ferromagnetic transformer or separate electronic. Main functions: - Choice of normal mode / timer - Configuration of the behavior in case of receiving commands ON / dimming - Configuration of predefined dimming values - Setting up of 15 scenarios Light Connection to the bus via red-black KNX connector. Supply voltage SELV 29 Vd.c from KNX bus. DIN rail mounting. Dimensions: 8 DIN modules.

	٦ 1	•	1 (• .	
1	Ach	nic	al t	Aatı	ires
- 1			41 I		

Brand	Legrand
Reference Standard	EN 50090 - EN 13321-1 e ISO/IEC 14543-3
Rated voltage	29 Vdc
Input current	12 mA
Modules	8 DIN
Protection class	IP 20 e IK 04
Plant type	KNX

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	3414970601506

Series

Technical documentation

? Instruction Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.