



002691



Controller KNX actuator for the control of solar protection devices (shutters, blinds). Equipped with 4 relay maximum load interlocked equal to 6A at 230 VAC Main functions: - Selection of the sun protection type (Venetian / shutter) - Sunscreen Movement timing configuration (up / down stroke time Reed orientation ...) - Save / recall of five scenarios - Save / recall the guard position solar - Selection behavior, sunscreen in case of wind / rain / frost alarm Connection to the bus via red-black KNX connector. Supply voltage SELV 29 Vd.c from KNX bus. DIN rail mounting. Dimensions: 4 DIN modules.

Technical features

Brand	Legrand
Reference Standard	EN 50090 - EN 13321-1 e ISO/IEC 14543-3
Rated voltage	29Vdc
Input current	12 mA
Modules	4 DIN
Plant type	KNX
Series	

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	3414970601605

Technical documentation

? ETS Project File

? DWG drawing

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.