



002693

legrand®

KNX binary interface equipped with 4 independent channels, allowable voltage of the input signal 0 - 265 V AC / DC. Usable for 'interfacing of traditional electromechanical controls the KNX bus and display returns status through display elements (LED) Main functions: - Switching or dimming - Control of sunscreens - Sending temperature values, levels ... - Sending multiple orders - Save / recall of scenarios - Sequential counter or differential Connection to the KNX bus via red-black KNX connector. Supply voltage SELV 29 V d.c from KNX bus. DIN rail mounting, size 2 DIN modules.

Technical features

Brand	Legrand
Reference Standard	EN 50090 - EN 13321-1 e ISO/IEC 14543-3
Rated voltage	29 Vdc
Input current	12 mA
Modules	2 DIN
Protection class	IP 20 e IK04
Plant type	KNX

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	3414970607768

Series

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product-Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.