



# 002694

KNX modular power supply. Connection to the bus via KNX Rossoneri connector. Input voltage: 230 V + 10% to 15%, 50 to 60 Hz. Output voltage: 29 V ± 1 V d.c. SELV. Output voltage Aux: 29 V ± 2 V d.c. SELV. output current: 320 mA. DIN rail mounting, dimensions 6 DIN modules

## Technical features

Brand                    Legrand

Rated voltage        Out: 29 V ± 1 Vdc SELV. In: 230 V +10%÷-15%,50÷60 Hz.

Frequency            50-60 Hz

Input current         640 mA

Modules                6 DIN

## Series

### Technical documentation

? Instruction Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

## Complete with



**002654**  
Universal 2 channel KNX dimmer with maxi...



**002692**  
KNX contact interface with 4 input chann...



**002693**  
KNX binary interface equipped with 4 ind...



**048918**  
Ceiling mounted double technology KNX se...



**048919**  
Ceiling mounted KNX PIR sensor, IP20 pro...



**048921**  
Wall mounted KNX PIR sensor, IP55 protec...



**048922**  
Ceiling mounted double technology KNX se...