



002898

legrand®

KNX Coupler, designed for bidirectional data exchange between two KNX lines while ensuring galvanic isolation. It can be used as:

- Line coupler (for connecting a line to a main line);
- Backbone coupler (for connecting a main line to the backbone line);
- Repeater (for coupling two segments of the same line).

Operational modes and statuses can be diagnosed through 6 LEDs. Dual bus connection via red-black KNX connector. SELV 29 V DC power supply from the KNX bus. Dimensions: 2 DIN modules.

Technical features

Brand	Legrand
Rated voltage	29 Vd.c.
Input current	12 mA
Modules	2 DIN
Protection class	IP 20
Series	KNX

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	3414972968454

Technical documentation

? Technical sheet

? Instruction sheet

We, BTicino S.p.A. Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.