


003506



KNX modular power supply with RESET button and signaling LED for: -overload -Power supply -reset Bus connection via red black KNX connector. Input voltage: 120-230V at 50 ... 60 Hz. Output voltage: 29V + 2 / -1V d.c. SELV. Auxiliary output voltage 29V + 2 / 0V d.c. SELV. Output current: 320 mA. Installation on DIN rail, dimensions 7 DIN modules

Technical features

Reference Standard EN 50090 - EN 13321-1 e ISO/IEC 14543-3

Rated voltage 230Vac

Frequency 50/60 Hz

Rated power (VA) 22 VA

Modules 7 DIN

Protection class IP 20 e IK 04

Output 29 Vdc e 320 mA (bus KNX)

Plant type KNX

Series

Commercial data

Minimum quantity 1

Sales unit 1

EAN code 3414972052399

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.