

048422

legrand



Multi-application controller with KNX 16 inputs and 16 outputs can realize multiple functions including: - Control ON-OFF lights or dimming via DALI protocol - Control of shutters - Control controllable outlets - Measurement of consumption of the connected loads (only on certain outputs) Each output can be controlled by traditional electromechanical devices or KNX devices and can be configured to operate according to three operating profiles different. Connection to the bus via red-black KNX connector. Supply voltage 27-50 Vd.c. DIN rail mounting. Dimensions: 12 DIN modules.

Technical features

Brand	Legrand
Reference Standard	EN 50090 - EN 13321-1 e ISO/IEC 14543-3
Rated voltage	27-50 Vdc
Modules	12 DIN
Protection class	IP 20 e IK 04
Plant type	KNX
Series	

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	3245060484224

Technical documentation

? ETS Project File

? DWG drawing

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.