

GENERAL CATALOGUE

048922

□ legrand®



Ceiling mounted double technology KNX sensor, passive infrared (PIR), protection degree IP20. Ideal for installation in working areas (e.g. offices, conference and meeting rooms, hall, corridor...). Bus connection using a red-black KNX connector. SELV 29 Vdc supply voltage from KNX bus. Flush mounted false ceiling or masonry ceiling installation using flush mounting boxes or springs; ceiling mounted installation using accessory item 048875. White colour

Commercial data

Brand	Legrand	Minimum quantity	1
Reference Standard	EN 50090 - EN 13321-1 e ISO/IEC 14543-3	Sales unit	1
Rated voltage	29 Vdc	EAN code	32
Input current	16 mA		
Protection class	IP 20 e IK 04		
Dimensions	Esterno 102 mm - incasso 52 mm		
Plant type	KNX		

ales unit	1

3245060489229

Series

Technical documentation

? Instruction sheet

? Technical sheet

? ETS Project File

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



048875 Box for surface ceiling installation, c...

