



049031



KNX thermostat for the management of 2/4 or 2 tube fan-coil convectors with electric heater. Fitted with: 2 valve outputs, 3 fan-coil speed adjustment outputs, and 2 freely configurable inputs for window contact, dew point probe, badge contact... Main functions: - preservation of the ambient temperature through built-in or external temperature sensor - switching between manual and automatic sensor driven cooling/heating - selection of the operating mode using the onboard pushbutton - 3 speed fan control (automatic or manual) - measured temperature or configured set-point display, °C or °F - advanced fan control functions (kick fan, fan start...) Bus connection using a red-black KNX connector. Supply voltage 230 Vac. Semi-flush mounted wall installation. White colour

Technical features

Brand	Legrand
Rated voltage	29 V.d.c.
Height	86 mm
Width	86 mm
Lenght	96 mm
Series	

Technical documentation

? DWG drawing

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.