



049292

legrand®

KNX cable with double pair of twisted conductors (red-black and white-yellow). It may be installed side by side with the 230 V supply cable and is indicated for protruding and flush mounted installation, for installation inside conduits, in dry outdoor areas, provided that protection from sunlight is ensured. Test voltage: 4 kV rated diameter 6.1 mm. Length (in m): 500.

Technical features

Brand	Legrand
Reference Standard	Densità dei fumi: IEC 61304-2 Corrosività dei gas combustibili: IEC 60754-1/2
Length	500 m
Plant type	KNX
Series	

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	3414970320810

Technical documentation

[? Technical sheet](#)

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.