



# 424912

Moulded case circuit breaker DPX3 250 for photovoltaic. Voltage 1000V, rated current 100A, breaking capacity 20kA, version 4P

## Technical features

Brand	Legrand
Reference Standard	IEC 60947-2
Rated voltage	1000Vac
Frequency	50-60Hz
Input current	100A
Breaking capacity ICU	20kA
Poles	4P
Protection class	IP30
Height	205mm
Width	140mm
Depth	116mm
Series	DPX3

## Commercial data

Minimum quantity	1
Sales unit	1
EAN code	3414972884983

## Technical documentation

? Instruction sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.