



424930

Moulded case circuit breaker DPX3 3P for photovoltaic $I_n = 320A$,
 $U_e = 1000V_{ac}$, $I_{cu} = 25kA$

Technical features

Brand	Legrand
Reference Standard	CEI EN 60947-2
Rated voltage	1000Vac
Frequency	50-60Hz
Input current	320A
Breaking capacity ICU	36kA
Poles	3P
Protection class	IP30
Height	290mm
Width	105mm
Depth	110mm
Series	Megabreak

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	3414972885065

Technical documentation

? Instruction sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.