



## MWS3A-KNX

legrand

Presence sensor. MW (microwave) detection, range up to 23m. Flat and compact sensor with adjustable head for special applications - IP 40. Recommended fixing height: 2,8m. Fixes directly in suspended ceiling with springs (supplied).

### Technical features

Brand	Legrand
Reference Standard	EMC-2014/30/EU, LVD-2014/35/EU
Rated voltage	30 VDC bus KNX
Input current	28.8mA
Protection class	IP40
Depth	92mm
Diameter	85mm
Installation height	2,6metri
Operating temperature	-10 C + 35 °C
Weight	150
Series	KNX

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.