

50400271-2400



Data Center straight elements (IP40). Aluminium conductors and windows on both sides (3+3, step 800mm) - In=160A - IP40 - length 2,4m

Technical features

Brand	BTicino
Input current	160A
Protection class	IP40
Lenght	2.4m
Series	

Technical documentation

? Instruction Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



50401001
Right feed unit from cabinet to transform...



50401121
Right feed unit (BIG) for busbar in AI M...



50401011
Left feed unit from cabinet to transform...



50401131
Left feed unit (BIG) for busbar in AI MR...