



50401012

bticino

Left feed unit from cabinet to transformers for busbar in Al
MR250 - In=250A - IP55

Technical features

Brand	BTicino
Reference Standard	CEI EN 61439-6
Rated voltage	1000Vac
Input current	250A
Protection class	IP55
Series	MR

Technical documentation

[↓ Installation manual](#)[↓ Instruction Sheet](#)

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with**50400142**Straight element MR250
Al with 1+1 outlet...**50400152**Straight element MR250
Al with 2+2 outlet...**50400102**Straight element MR250
Al with 3+3 outlet...**50400252**Straight element MR250
Al with 5 outlets...**50400242**Straight element MR250
Al without outlet...**50400112**Straight element MR250
Al without outlet...**50400122**Straight element MR250
Al without outlet...**50400262-
2400**Data Center straight
elements (IP40). Al...**50400262**Data Center straight
elements (IP40). Al...**50400272-
1600**Data Center straight
elements (IP40). Al...**50400272-
2400**Data Center straight
elements (IP40). Al...