

51530116

Straight element MS63 4 conductors 3P+N - In=63A - IP55 - length 2m



Technical features

Reference Standard	CEI EN 61439-6
Rated voltage	400Vac
Input current	63A
Poles	3P+N
Protection class	IP40/55
Length	2m
Compartments	2+2

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8033777041527

Series

Technical documentation

? Installation Manual

? Installation Manual

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



51511051
Right feed unit for busbar
MS63 e MS100 ...



51511151
Intermediate feed unit for
busbar MS63 e...



51511052
Left feed unit for busbar
MS63 e MS100 -...