



FK2AAACBA



Cast resin transformer, type AoAk - insulating class 12kV- P= 1000kVA - Vprim= 10kV - Vsec= 400V - Po= 1550W - Pk= 9000W. Cooling method: AN - Conductor type: Aluminium - Conductor mass= 680kg - Core type: CRGO - Magnetic Core mass= 1680 kg - Total mass= 2900 kg

Technical features

Brand	BTicino
Reference Standard	EN 50588-1
Rated voltage	10kV/400V
Rated power (VA)	1000kVA
Height	1950mm
Width	1650mm
Depth	1000mm
Series	GreenT.he

Technical documentation

? Installation manual

? Product Environmental Profile

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.