



# HN5AIDQBA



Cast resin transformer - insulation class 36kV- P= 2000kVA -  
 $V_{prim}= 33kV$  -  $V_{sec}= 400V$  -  $P_o= 2691W$  -  $P_k= 17600W$  -  $U_k= 8\%$

## Technical features

Brand	BTicino
Reference Standard	IEC 60076-11 e EN 50708
Rated voltage	33kV-400V
Frequency	50Hz
Rated power (VA)	2000kVA
Height	2.45m
Width	1.7m
Lenght	2.15m
Series	GreenT.he Cast resin transformers

## Technical documentation

? Installation manual

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.