

BTICINO > Door entry system > 2 wires system > Accessories







336904

Specific BUS/SCS cable, unshielded, consisting of a white external sheath and 2 x 0.50 mm² brown and brown/white twisted flexible conductors. Insulation 400 V. In compliance with the standards: EN50575 EN60811, EN50289, EN50290, EN60228, EN50265-2-1, EN50395, EN50396 as described in the IMQ CPT 062 document. Cable suitable for underground installation inside appropriate conduits (for the details see the technical sheet). Coil length 200 m. Class of reaction to fire according to the CPR Regulation: Eca.

Technical features

Length	200 metri
Series	Accessories

Documentation

-  [Scheda Tecnica](#)
-  [Technical guide](#)
-  [My Home guidelines](#)
-  [Catalogue](#)
-  [Living Now english catalogue](#)

Certificazioni



Related products



346020

Additional power supply to be used to supply entrance panels and internal units locally. 2 DIN modul...



E49

Compact power supply for Temperature control and Automation systems - input 230 Vac, output 27 Vdc -...



E46ADCN

Power supply - input 230 Vac, output 27 Vdc SELV - maximum consumption 450 mA – DIN rail mounted mod...



E46ADCN/127

Power supply - input 127 Vac, output 27 Vdc SELV - space requirement 8 DIN modules - for flush mount...