

BTICINO > Door entry systems > Accessories for 2 wires system > Accessories



336905

Specific BUS/SCS cable, unshielded, consisting of a white external sheath and 2 x 0.50 mm² brown and brown/white twisted flexible conductors. Halogen-free Low toxicity cable; ideal for applications where fire safety is particularly critical. Insulation 400 V. In compliance with the standards: EN 50575 EN60811, EN50289, EN50290, EN60228, 50265-2- 1, EN50395, EN50396 as described in the IMQ CPT 062 document Cable not suitable for underground installation. Coil length 200 m. Class of reaction to fire according to the CPR regulation: Cca-s1b,d1,a1.

Technical features

Brand	BTicino
Length	200m
Series	Accessories

Documentation

[!\[\]\(faf942dc3e59ce8eb64b4ac481eca7e0_img.jpg\) Technical Data Sheet](#)[!\[\]\(cf531ed27e91483460120fcc057b3901_img.jpg\) Declaration of Performance](#)

Related products



346020

Additional power supply to be used to supply entrance panels and internal units locally. 2 DIN modul...



E49

Compact power supply for Temperature control and Automation systems - input 230 Vac, output 27 Vdc -...



E46ADCN

Power supply - input 230 Vac, output 27 Vdc SELV - maximum consumption 450 mA - DIN rail mount...



E46ADCN/127

Power supply - input 127 Vac, output 27 Vdc SELV - space requirement 8 DIN modules - for flush mount...