

BTICINO > Solution for energy efficiency > Lighting control - BUS - SCS System > Sensors



BMSE3003

SCS sensor with double technology: passive infrared ed ultrasound, for presence of people and luminance level detection, flush mount installation in the ceiling with springs or box, surface installation with box item 048875, protection degree IP20, terminal connection and RJ45, infrared covering area diameter 8 m (50 mq) for an height of 2.5 m, ultrasound covering area diameter 11 m (95 mq) for an height of 2.5 m, maximum installation height 6 m, power supply 27 Vdc from Bus, consumption 17 mA, setting by remote control item BMSO4003 and BMSO4001 or with specific configuration software of the luminance level from 5 lux to 1275 lux, delay time from 30 s to 255 h, with pushbutton for Push&Learn procedure

Technical features

Brand	BTicino
Rated voltage	27Vdc
Rated current	17mA
Protection index	IP20
Depth	62mm
Diameter	120mm
Cabling	BUS-SCS
Illuminance level	5 a 1275 lux
Operating temperature	- 5 C + 45°C
Color	Biaco
Series	MyHome

Documentation

[!\[\]\(faf942dc3e59ce8eb64b4ac481eca7e0_img.jpg\) Instruction Sheet](#)[!\[\]\(cf531ed27e91483460120fcc057b3901_img.jpg\) DWG drawing](#)

Related products



088240

Allows you to adjust the time delay, the brightness threshold and the detection sensitivity
Possibi...



BMSO4003

Remote control for the configuration (base) with infrared receiver and transmitter, allow the settin...