

BTICINO > Low voltage energy distribution > Switchboards > LINEA WALL wall mounted switchboards



F305PT12

Wall mounted switchboard with box and transparent door, 12 x DIN35 modules (235x250x105mm). Compliance with regulations IEC 60670-24 , CEI 23-48 , CEI 23-49, CEI 61439-3. IP40 and IK07 (6 joule) protection index. Material in thermoplastic resin. Insulating class II. RAL 9003 white wall mounted box. Operating temperature: -10 to 60 °C. Resistance to abnormal heat and fire (EN 60695-2-11): 650 °C. DIN35 rail type: Galvanized steel. Preset cut-outs for pipes (diameter) 16-32mm. Reversible door opening. Wall mounted box supplied

Technical features

Protection index	IP40/IK07
Height	235mm
Width	250mm
Depth	112mm
N° of modules	8
Standard reference	IEC 60670-24 , CEI 23-48 , CEI 23-49, CEI 61439-3
Rated power W	22W
Series	Linea Wall

Documentation

 [Technical data sheet](#)

Certificazioni




Related products



F305B12

RAL9003 white door for LINEA WALL wall mounted switchboards, 12 x DIN35 modules (235x250x105mm).
Com...



F215FP

Blanking module front cover with 6.5 DIN modules with knockouts every 1/2 module



F305C1

Key door lock for Linea Wall switchboards with 8 - 72 DIN modules



F305KM

Wall fixing brackets for switchboards with 12 - 72 DIN modules