

BTICINO &gt; Low voltage energy distribution &gt; Distribution boards and enclosures &gt; Switchboards &gt; LINEA WALL wall mounted switchboards




## F305PT72

Wall mounted switchboard with box and transparent door, 72 x DIN35 modules (750x450x150mm). Compliance with regulations IEC 60670-24 , CEI 23-48 , CEI 23-49, CEI 61439-3. IP40 and IK07 (6 joule) protection index. Material in thermoplastic resin. Insulating class II. RAL 9003 white wall mounted box. Operating temperature: -10 to 60 °C. Resistance to abnormal heat and fire (EN 60695-2-11): 650 °C. DIN35 rail type: Galvanized steel. Preset cut-outs for pipes (diameter) 16-32mm. Reversible door opening. Wall mounted box supplied

### Technical features

Brand	BTicino
Standard reference	IEC 60670-24 , CEI 23-48 , CEI 23-49, CEI 61439-3
Rated power W	68W
N° of modules	4x18
Protection index	IP40/IK07
Height	750mm
Width	450mm
Depth	150mm
Series	Linea Wall

### Documentation

 [Technical Data Sheet](#)

### Certificazioni




## Related products



### F305B72

RAL9003 white door for LINEA WALL wall mounted switchboards, 72 x DIN35 modules (750x450x150mm).  
Com...



### F215FP

Blanking module front cover with 6.5 DIN modules with knockouts every 1/2 module



### F305C1

Key door lock for Linea Wall switchboards with 8 - 72 DIN modules



### F305KM

Wall fixing brackets for switchboards with 12 - 72 DIN modules



### F305PF18

Perforated device holder plate for 36 - 54 and 72 DIN module switchboards - height 145 mm



### F305PP18

Solid plate for 36 - 54 and 72 DIN module switchboards - height 145 mm



### F305TP

Document holder pocket