



## FN84C10

BTDIN60 - 4P thermal-magnetic curve C - In= 10A - Icn= 6kA - Vn= 400 Vac - 4 modules

### Technical features

|                             |                |
|-----------------------------|----------------|
| Brand                       | BTicino        |
| Standard reference          | CEI EN 60898-1 |
| Rated voltage               | 400Vac         |
| Rated current               | 10A            |
| Rated breaking capacity Icn | 6kA            |
| Tripping curve              | C              |
| N° of modules               | 4              |
| N° of poles                 | 4P             |
| Protection index            | IP20           |
| Height                      | 83mm           |
| Width                       | 71.2mm         |

### Documentation

- [DWG drawing](#)
- [Technical Data Sheet](#)
- [Environment. Product Declaration](#)
- [Tripping curves](#)

### Certifications



Depth 76mm

Max section 25/35mmq

Series Btdin

## Related products



### G43A32

Earth leakage module  
4P - type A - In= 32A -  
Idn= 30mA - Vn= 400  
Vac



### G43F32

Earth leakage module  
4P - type F - In= 32A -  
Idn= 30mA - Vn= 400  
Vac



### G43AC32

Earth leakage module  
4P - type AC - In= 32A -  
Idn= 30mA - Vn= 400  
Vac