

BTICINO &gt; Low voltage energy distribution &gt; Circuit breakers for protection &gt; BTDIN miniature circuit breakers &gt; BTDIN100 Thermal magnetic circuit breakers Icu=16kA



## FT82C40


BTDIN160 - 2P thermal-magnetic curve C - In= 40A - Icu= 16kA - Vn= 400 Vac - 2 modules

### Technical features

Brand	BTicino
Standard reference	CEI EN 60947-2
Rated voltage	400Vac
Rated current	40A
Ultimate breaking capacity Icu	16kA
Tripping curve	C
N° of modules	2
N° of poles	2P
Protection index	IP20
Height	83mm
Width	35.6mm
Depth	76mm
Max section	25/35mmq
Series	Btdin

### Documentation

 [Technical sheet](#)

 [DWG drawing](#)

 [Tripping curves](#)

## Related products



### G23A63

Earth leakage module  
2P - type A - In= 63A -  
Idn= 30mA - Vn=  
230/400 Vac



### G23F63

Earth leakage module  
2P - type F - In= 63A -  
Idn= 30mA - Vn=  
230/400 Vac



### G23AC63

Earth leakage module  
2P - type AC - In= 63A -  
Idn= 30mA - Vn=  
230/400 Vac