

BTICINO &gt; Low voltage energy distribution &gt; Circuit breakers for protection &gt; BTDIN miniature circuit breakers &gt; BTDIN100 Thermal magnetic circuit breakers Icu=16kA




## FT82D100


BTDIN160 - 2P thermal-magnetic curve D - In= 100A - Icu= 16kA  
- Vn= 400 Vac - 3 modules


### Technical features

Brand	BTicino
Standard reference	CEI EN 60947-2
Rated voltage	400Vac
Rated current	100A
Ultimate breaking capacity Icu	16kA
Tripping curve	D
N° of modules	3
N° of poles	2P
Protection index	IP20
Height	83mm
Width	53.4mm
Depth	76mm
Max section	50/70mmq
Series	Btdin

### Documentation

 [Instruction Sheet](#)

 [DWG drawing](#)

 [Tripping curves](#)

## Related products



### G23XF125

Earth leakage module  
2P - type F - In= 125A -  
Idn= 30mA - Vn=  
230/400 Vac



### G23XAC125

Earth leakage module  
2P - type AC - In= 125A  
- Idn= 30mA - Vn=  
230/400 Vac



### G27XF125

Earth leakage module  
2P - type F - In= 125A -  
Vn= 230/400 Vac - time  
and current setting