

BTICINO > Low voltage energy distribution > Circuit breakers for protection > BTDIN miniature circuit breakers > BTDIN100 Thermal magnetic circuit breakers Icu=25kA




FV82C125

BTDIN250 - 2P thermal-magnetic curve C - In= 125A - Icu= 25kA
- Vn= 400Vac - 3 modules

Technical features

Brand	BTicino
Standard reference	CEI EN 60947-2
Rated voltage	400Vac
Rated current	125A
Ultimate breaking capacity Icu	25kA
Tripping curve	C
N° of modules	3
N° of poles	2P
Protection index	IP20
Height	83mm
Width	53.4mm
Depth	76mm
Max section	50/70mmq
Series	Btdin

Documentation

 [Instruction Sheet](#)

 [DWG drawing](#)

 [Tripping curves](#)

Related products



G23XF125

Earth leakage module
2P - type F - $I_n = 125A$ -
 $I_{dn} = 30mA$ - $V_n =$
230/400 Vac



G23XAC125

Earth leakage module
2P - type AC - $I_n = 125A$
- $I_{dn} = 30mA$ - $V_n =$
230/400 Vac



G27XF125

Earth leakage module
2P - type F - $I_n = 125A$ -
 $V_n = 230/400$ Vac - time
and current setting