

BTICINO > Low voltage energy distribution > Circuit breakers for protection > BTDIN miniature circuit breakers > BTDIN100 Thermal magnetic circuit breakers Icu=25kA




FV82C40

BTDIN250 - 2P thermal-magnetic curve C - In= 40A - Icu= 25kA - Vn= 400Vac - 2 modules

Technical features

Brand	BTicino
Standard reference	CEI EN 60947-2
Rated voltage	400Vac
Rated current	40A
Ultimate breaking capacity Icu	25kA
Tripping curve	C
N° of modules	2
N° of poles	2P
Protection index	IP20
Height	83mm
Width	35.6mm
Depth	76mm
Max section	25/35mmq
Series	Btdin

Documentation

 [Instruction Sheet](#)

 [DWG drawing](#)

 [Tripping curves](#)

Related products



G23XA63

Earth leakage module
2P - type A - In= 63A -
Idn= 30mA - Vn=
230/400 Vac



G23XF63

Earth leakage module
2P - type F - In= 63A -
Idn= 30mA - Vn=
230/400 Vac



G23XAC63

Earth leakage module
2P - type AC - In= 63A -
Idn= 30mA - Vn=
230/400 Vac



G27XF63

Earth leakage module
2P - type F - In= 63A -
Vn= 230/400 Vac - time
and current setting