

BTICINO &gt; Low voltage energy distribution &gt; Circuit breakers for protection &gt; BTDIN miniature circuit breakers &gt; BTDIN100 Thermal magnetic circuit breakers Icu=25kA



## FV84C40


BTDIN250 - 4P thermal-magnetic curve C - In= 40A - Icu= 25kA - Vn= 400Vac - 4 modules


### Technical features

Brand	BTicino
Standard reference	CEI EN 60947-2
Rated voltage	400Vac
Rated current	40A
Ultimate breaking capacity Icu	25kA
Tripping curve	C
N° of modules	4
N° of poles	4P
Protection index	IP20
Height	83mm
Width	71.2mm
Depth	76mm
Max section	25/35mmq
Series	Btdin

### Documentation

 [Instruction Sheet](#)

 [DWG drawing](#)

 [Tripping curves](#)

## Related products



### G43XA63

Earth leakage module  
4P - type A - In= 63A -  
Idn= 30mA - Vn= 400  
Vac



### G43XF63

Earth leakage module  
4P - type F - In= 63A -  
Idn= 30mA - Vn= 400  
Vac



### G43XAC63

Earth leakage module  
4P - type AC - In= 63A -  
Idn= 30mA - Vn= 400  
Vac



### G47XF63

Earth leakage module  
4P - type F - In= 63A -  
Vn= 400 Vac - time and  
current setting