

BTICINO > Low voltage energy distribution > Circuit breakers for protection > BTDIN miniature circuit breakers > BTDIN500 Thermal magnetic circuit breakers Icu=50kA



FX82C16

BTDIN500 - 2P thermal-magnetic curve C - In= 16A - Icu= 50kA - Vn= 400Vac - 3 modules

Technical features

Brand	BTicino
Standard reference	CEI EN 60947-2
Rated voltage	400Vac
Rated current	16A
Ultimate breaking capacity Icu	50kA
Tripping curve	C
N° of modules	3
N° of poles	2P
Protection index	IP20
Height	83mm
Width	53.4mm
Depth	76mm
Max section	50/70mmq
Series	Btdin

Documentation

 [Instruction Sheet](#)

 [DWG drawing](#)

 [Tripping curves](#)

Related products



G23XA63

Earth leakage module
2P - type A - In= 63A -
Idn= 30mA - Vn=
230/400 Vac



G23XF63

Earth leakage module
2P - type F - In= 63A -
Idn= 30mA - Vn=
230/400 Vac



G23XAC63

Earth leakage module
2P - type AC - In= 63A -
Idn= 30mA - Vn=
230/400 Vac



G27XF63

Earth leakage module
2P - type F - In= 63A -
Vn= 230/400 Vac - time
and current setting