

BTICINO > Low voltage energy distribution > BTDIN miniature circuit breakers > Combinable earth leakage modules



G23F32

Earth leakage module 2P - type F - $I_n = 32A$ - $I_{dn} = 30mA$ - $V_n = 230/400 Vac$


Technical features

Protection index	IP20
Max section	25/35mmq
Height	83mm
Width	35.6mm
Depth	76mm
N° of modules	2
Standard reference	CEI EN 61009-1
N° of poles	2P
Rated voltage	230/400Vac
Earth leakage type	F
Earth leakage rated current	0.03A
Rated current	32A
Series	Btdin

Documentation

 [Technical Data Sheet](#)

 [Instructions Sheet](#)

 [Catalogue BTDIN](#)

Certificazioni



Related products



FH82D10

BTDIN100 - 2P thermal-magnetic curve D - In= 10A - Icn= 10kA - Vn= 400 Vac - 2 modules



FN82C4

BTDIN60 - 2P thermal-magnetic curve C - In= 4A - Icn= 6kA - Vn= 400 Vac - 2 modules



FA81NC16

BTDIN45 - 1P+N thermal-magnetic curve C - In= 16A - Icn= 4,5kA - Vn= 230 Vac - 2 modules



FN81NC16

BTDIN60 - 1P+N thermal-magnetic curve C - In= 16A - Icn= 6kA - Vn= 230 Vac - 2 modules



FT82C20

BTDIN160 - 2P thermal-magnetic curve C - In= 20A - Icu= 16kA - Vn= 400 Vac - 2 modules



FA82C32

BTDIN45 - 2P thermal-magnetic curve C - In= 32A - Icn= 4,5kA - Vn= 400 Vac - 2 modules



FN82B16

BTDIN60 - 2P thermal-magnetic curve B - In= 16A - Icn= 6kA - Vn= 400 Vac - 2 modules



FV82C6

BTDIN250 - 2P thermal-magnetic curve C - In= 6A - Icu= 25kA - Vn= 400Vac - 2 modules



FH82C16

BTDIN100 - 2P thermal-magnetic curve C - In= 16A - Icn= 10kA - Vn= 400 Vac - 2 modules



FN82C2

BTDIN60 - 2P thermal-magnetic curve C - In= 2A - Icn= 6kA - Vn= 400 Vac - 2 modules