

BTICINO > Low voltage energy distribution > BTDIN miniature circuit breakers > Combinable earth leakage modules







G23F63

Earth leakage module 2P - type F - In= 63A - I_{dn}= 30mA - V_n= 230/400 Vac

Technical features

Protection index	IP20
Max section	25/35mmq
Height	83mm
Width	35.6mm
Depth	76mm
N° of modules	2
Standard reference	CEI EN 61009-1
N° of poles	2P
Rated voltage	230/400Vac
Earth leakage type	F
Earth leakage rated current	0.03A
Rated current	63A
Series	Btdin

Documentation

-  [Technical Data Sheet](#)
-  [Instructions Sheet](#)
-  [DWG drawing](#)
-  [Catalogue BTDIN](#)

Certificazioni



Related products



FN81NC50

BTDIN60 - 1P+N
thermal-magnetic curve
C - In= 50A - Icn= 6kA -
Vn= 230 Vac - 2
modules



FN82D50

BTDIN60 - 2P thermal-
magnetic curve D - In=
50A - Icn= 6kA - Vn=
400 Vac - 2 modules



FA81NC63

BTDIN45 - 1P+N
thermal-magnetic curve
C - In= 63A - Icn= 4,5kA
- Vn= 230 Vac - 2
modules



FH82C63

BTDIN100 - 2P thermal-
magnetic curve C - In=
63A - Icn= 10kA - Vn=
400 Vac - 2 modules



FN82B63

BTDIN60 - 2P thermal-
magnetic curve B - In=
63A - Icn= 6kA - Vn=
400 Vac - 2 modules



FT82C63

BTDIN160 - 2P thermal-
magnetic curve C - In=
63A - Icu= 16kA - Vn=
400 Vac - 2 modules



FH81NC40

BTDIN100 - 1P+N
thermal-magnetic curve
C - In= 40A - Icn= 10kA -
Vn= 230 Vac - 2
modules



FN81NC40

BTDIN60 - 1P+N
thermal-magnetic curve
C - In= 40A - Icn= 6kA -
Vn= 230 Vac - 2
modules



FN82D40

BTDIN60 - 2P thermal-
magnetic curve D - In=
40A - Icn= 6kA - Vn=
400 Vac - 2 modules



FA81NC50

BTDIN45 - 1P+N
thermal-magnetic curve
C - In= 50A - Icn= 4,5kA
- Vn= 230 Vac - 2
modules