




G23XA63

Earth leakage module 2P - type A - $I_n = 63A$ - $I_{dn} = 30mA$ - $V_n = 230/400 Vac$

Technical features

Brand	BTicino
Standard reference	CEI EN 60947-2
Rated voltage	230-400Vac
Rated current	63A
Earth leakage rated current	0.03A
Earth leakage type	A
N° of modules	2
N° of poles	2P
Protection index	IP20
Height	83mm
Width	35.6mm

Documentation

 [Technical Data Sheet](#)

Certifications



Depth 76mm

Max section 50/70mmq

Series Btdin

Related products



FV82C63

BTDIN250 - 2P thermal-magnetic curve C - In= 63A - Icu= 25kA - Vn= 400Vac - 2 modules



FV82D63

BTDIN250 - 2P thermal-magnetic curve D - In= 63A - Icu= 25kA - Vn= 400Vac - 2 modules



FX82C25

BTDIN500 - 2P thermal-magnetic curve C - In= 25A - Icu= 50kA - Vn= 400Vac - 3 modules



FV81ND63

BTDIN250 - 1P+N thermal-magnetic curve D - In= 63A - Icu= 25kA - Vn= 400Vac - 2 modules



FV82C50

BTDIN250 - 2P thermal-magnetic curve C - In= 50A - Icu= 25kA - Vn= 400Vac - 2 modules



FX82C63

BTDIN500 - 2P thermal-magnetic curve C - In= 63A - Icu= 50kA - Vn= 400Vac - 3 modules



FX82C20

BTDIN500 - 2P thermal-magnetic curve C - In= 20A - Icu= 50kA - Vn= 400Vac - 3 modules



FV82D6

BTDIN250 - 2P thermal-magnetic curve D - In= 6A - Icu= 25kA - Vn= 400Vac - 2 modules



FV82C40

BTDIN250 - 2P thermal-magnetic curve C - In= 40A - Icu= 25kA - Vn= 400Vac - 2 modules



FX82C50

BTDIN500 - 2P thermal-magnetic curve C - In= 50A - Icu= 50kA - Vn= 400Vac - 3 modules