

BTICINO > Low voltage energy distribution > BTDIN miniature circuit breakers > Combinable earth leakage modules



G23XAC63


Earth leakage module 2P - type AC - In= 63A - I_{dn}= 30mA - V_n= 230/400 Vac

Technical features

Protection index	IP20
Max section	50/70mmq
Height	83mm
Width	35.6mm
Depth	76mm
N° of modules	2
Standard reference	CEI EN 60947-3
N° of poles	2P
Rated voltage	230/400Vac
Earth leakage type	AC
Earth leakage rated current	0.03A
Rated current	63A
Series	Btdin

Documentation

 [Technical Data Sheet](#)

 [Catalogue BTDIN](#)

Certificazioni



Related products



FV82C63

BTDIN250 - 2P thermal-magnetic curve C - In= 63A - Icu= 25kA - Vn= 400Vac - 2 modules



FX82C25

BTDIN500 - 2P thermal-magnetic curve C - In= 25A - Icu= 50kA - Vn= 400Vac - 3 modules



FV82C50

BTDIN250 - 2P thermal-magnetic curve C - In= 50A - Icu= 25kA - Vn= 400Vac - 2 modules



FX82C63

BTDIN500 - 2P thermal-magnetic curve C - In= 63A - Icu= 50kA - Vn= 400Vac - 3 modules



FX82C20

BTDIN500 - 2P thermal-magnetic curve C - In= 20A - Icu= 50kA - Vn= 400Vac - 3 modules



FV82C40

BTDIN250 - 2P thermal-magnetic curve C - In= 40A - Icu= 25kA - Vn= 400Vac - 2 modules



FX82C50

BTDIN500 - 2P thermal-magnetic curve C - In= 50A - Icu= 50kA - Vn= 400Vac - 3 modules



FX82C16

BTDIN500 - 2P thermal-magnetic curve C - In= 16A - Icu= 50kA - Vn= 400Vac - 3 modules



FX82C40

BTDIN500 - 2P thermal-magnetic curve C - In= 40A - Icu= 50kA - Vn= 400Vac - 3 modules



FX82C10

BTDIN500 - 2P thermal-magnetic curve C - In= 10A - Icu= 50kA - Vn= 400Vac - 3 modules