

BTICINO > Low voltage energy distribution > BT DIN miniature circuit breakers > Combinable earth leakage modules




G27XF125

Earth leakage module 2P - type F - $I_n = 125A$ - $V_n = 230/400\text{ Vac}$ - time and current setting


Technical features

Protection index	IP20
Max section	50/70mmq
Height	83mm
Width	71.1mm
Depth	76mm
N° of modules	4
Standard reference	CEI EN 60947-18
N° of poles	2P
Rated voltage	230/400Vac
Earth leakage type	F
Earth leakage rated current	0.3-0.5-1A
Rated current	125A
Series	Btdin

Documentation

 [Technical Data Sheet](#)

 [Instructions Sheet](#)

 [Catalogue BT DIN](#)

Related products



FT82C125

BTDIN160 - 2P thermal-magnetic curve C - In= 125A - Icu= 16kA - Vn= 400 Vac - 3 modules



FT82D80

BTDIN160 - 2P thermal-magnetic curve D - In= 80A - Icu= 16kA - Vn= 400 Vac - 3 modules



FT82C100

BTDIN160 - 2P thermal-magnetic curve C - In= 100A - Icu= 16kA - Vn= 400 Vac - 3 modules



FT82D125

BTDIN160 - 2P thermal-magnetic curve D - In= 125A - Icu= 16kA - Vn= 400 Vac - 3 modules



FV82C80

BTDIN250 - 2P thermal-magnetic curve C - In= 80A - Icu= 25kA - Vn= 400Vac - 3 modules



FT82D100

BTDIN160 - 2P thermal-magnetic curve D - In= 100A - Icu= 16kA - Vn= 400 Vac - 3 modules



FV82C125

BTDIN250 - 2P thermal-magnetic curve C - In= 125A - Icu= 25kA - Vn= 400Vac - 3 modules



FT82C80

BTDIN160 - 2P thermal-magnetic curve C - In= 80A - Icu= 16kA - Vn= 400 Vac - 3 modules



FV82C100

BTDIN250 - 2P thermal-magnetic curve C - In= 100A - Icu= 25kA - Vn= 400Vac - 3 modules