

BTICINO &gt; Low voltage energy distribution &gt; BT DIN miniature circuit breakers &gt; Combinable earth leakage modules







## G33A63

Earth leakage module 3P - type A - In= 63A - IΔn= 30mA - Vn= 400 Vac

### Technical features

Protection index	IP20
Max section	25/35mmq
Height	83mm
Width	53.4mm
Depth	76mm
N° of modules	3
Standard reference	CEI EN 61009-1
N° of poles	3P
Rated voltage	400Vac
Earth leakage type	A
Earth leakage rated current	0.03A
Rated current	63A
Series	Btdin

### Documentation

-  [Technical Data Sheet](#)
-  [Instructions Sheet](#)
-  [DWG drawing](#)
-  [Catalogue BT DIN](#)

### Certificazioni



## Related products



**FT83C63**

BTDIN160 - 3P thermal-magnetic curve C - In= 63A - Icu= 16kA - Vn= 400 Vac - 3 modules



**FH83D40**

BTDIN100 - 3P thermal-magnetic curve D - In= 40A - Icn= 10kA - Vn= 400 Vac - 3 modules



**FN83D40**

BTDIN60 - 3P thermal-magnetic curve D - In= 40A - Icn= 6kA - Vn= 400 Vac - 3 modules



**FA83C50**

BTDIN45 - 3P thermal-magnetic curve C - In= 50A - Icn= 4,5kA - Vn= 400 Vac - 3 modules



**FN83B50**

BTDIN60 - 3P thermal-magnetic curve B - In= 50A - Icn= 6kA - Vn= 400 Vac - 3 modules



**FT83C50**

BTDIN160 - 3P thermal-magnetic curve C - In= 50A - Icu= 16kA - Vn= 400 Vac - 3 modules



**FH83C63**

BTDIN100 - 3P thermal-magnetic curve C - In= 63A - Icn= 10kA - Vn= 400 Vac - 3 modules



**FN83C63**

BTDIN60 - 3P thermal-magnetic curve C - In= 63A - Icn= 6kA - Vn= 400 Vac - 3 modules



**FA83C40**

BTDIN45 - 3P thermal-magnetic curve C - In= 40A - Icn= 4,5kA - Vn= 400 Vac - 3 modules



**FN83B40**

BTDIN60 - 3P thermal-magnetic curve B - In= 40A - Icn= 6kA - Vn= 400 Vac - 3 modules