

BTICINO > Low voltage energy distribution > BT DIN miniature circuit breakers > Combinable earth leakage modules






G33AC63

Earth leakage module 3P - type AC - In= 63A - IΔn= 30mA - Vn= 400 Vac

Technical features

Protection index	IP20
Max section	25/35mmq
Height	83mm
Width	53.4mm
Depth	76mm
N° of modules	3
Standard reference	CEI EN 61009-1
N° of poles	3P
Rated voltage	400Vac
Earth leakage type	AC
Earth leakage rated current	0.03A
Rated current	63A
Series	Btdin

Documentation

-  [Technical Data Sheet](#)
-  [Instructions Sheet](#)
-  [Catalogue BT DIN](#)

Certificazioni



Related products



FH83C50

BTDIN100 - 3P thermal-magnetic curve C - In= 50A - Icn= 10kA - Vn= 400 Vac - 3 modules



FH83D63

BTDIN100 - 3P thermal-magnetic curve D - In= 63A - Icn= 10kA - Vn= 400 Vac - 3 modules



FH83C40

BTDIN100 - 3P thermal-magnetic curve C - In= 40A - Icn= 10kA - Vn= 400 Vac - 3 modules



FH83D50

BTDIN100 - 3P thermal-magnetic curve D - In= 50A - Icn= 10kA - Vn= 400 Vac - 3 modules



FT83C63

BTDIN160 - 3P thermal-magnetic curve C - In= 63A - Icu= 16kA - Vn= 400 Vac - 3 modules



FH83D40

BTDIN100 - 3P thermal-magnetic curve D - In= 40A - Icn= 10kA - Vn= 400 Vac - 3 modules



FT83C50

BTDIN160 - 3P thermal-magnetic curve C - In= 50A - Icu= 16kA - Vn= 400 Vac - 3 modules



FH83C63

BTDIN100 - 3P thermal-magnetic curve C - In= 63A - Icn= 10kA - Vn= 400 Vac - 3 modules



FT83C40

BTDIN160 - 3P thermal-magnetic curve C - In= 40A - Icu= 16kA - Vn= 400 Vac - 3 modules