

BTICINO > Low voltage energy distribution > Circuit breakers for protection > BTDIN miniature circuit breakers > Combinable earth leakage modules






G43A32

Earth leakage module 4P - type A - In= 32A - Idn= 30mA - Vn= 400 Vac

Technical features

Brand	BTicino
Standard reference	CEI EN 61009-1
Rated voltage	400Vac
Rated current	32A
Earth leakage rated current	0.03A
Earth leakage type	A
N° of modules	2
N° of poles	4P
Protection index	IP20
Height	83mm
Width	35.6mm
Depth	76mm
Max section	25/35mmq
Series	Btdin

Documentation

-  [Technical Data Sheet](#)
-  [Instruction Sheet](#)
-  [Tripping curves](#)

Certificazioni



We, Bticino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in Bticino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". Bticino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Related products



FA84C10

BTDIN45 - 4P thermal-magnetic curve C - In= 10A - Icn= 4,5kA - Vn= 400 Vac - 4 modules



FN84D20

BTDIN60 - 4P thermal-magnetic curve D - In= 20A - Icn= 6kA - Vn= 400 Vac - 4 modules



FH84C25

BTDIN100 - 4P thermal-magnetic curve C - In= 25A - Icn= 10kA - Vn= 400 Vac - 4 modules



FV84C10

BTDIN250 - 4P thermal-magnetic curve C - In= 10A - Icu= 25kA - Vn= 400Vac - 4 modules



FN84B10

BTDIN60 - 4P thermal-magnetic curve B - In= 10A - Icn= 6kA - Vn= 400 Vac - 4 modules



FN84C25

BTDIN60 - 4P thermal-magnetic curve C - In= 25A - Icn= 6kA - Vn= 400 Vac - 4 modules



FA84C32

BTDIN45 - 4P thermal-magnetic curve C - In= 32A - Icn= 4,5kA - Vn= 400 Vac - 4 modules



FT84C16

BTDIN160 - 4P thermal-magnetic curve C - In= 16A - Icu= 16kA - Vn= 400 Vac - 4 modules



FH84D16

BTDIN100 - 4P thermal-magnetic curve D - In= 16A - Icn= 10kA - Vn= 400 Vac - 4 modules



FV84C6

BTDIN250 - 4P thermal-magnetic curve C - In= 6A - Icu= 25kA - Vn= 400Vac - 4 modules