

BTICINO > Low voltage energy distribution > BTDIN miniature circuit breakers > Combinable earth leakage modules






G43F32

Earth leakage module 4P - type F - In= 32A - Idn= 30mA - Vn= 400 Vac

Technical features

Protection index	IP20
Max section	25/35mmq
Height	83mm
Width	35.6mm
Depth	76mm
N° of modules	2
Standard reference	CEI EN 61009-1
N° of poles	4P
Rated voltage	400Vac
Earth leakage type	F
Earth leakage rated current	0.03A
Rated current	32A
Series	Btdin

Documentation

-  [Technical Data Sheet](#)
-  [Instructions Sheet](#)
-  [Catalogue BTDIN](#)

Certificazioni



Related products



FN84C10

BTDIN60 - 4P thermal-magnetic curve C - In= 10A - Icn= 6kA - Vn= 400 Vac - 4 modules



FA84C16

BTDIN45 - 4P thermal-magnetic curve C - In= 16A - Icn= 4,5kA - Vn= 400 Vac - 4 modules



FN84D25

BTDIN60 - 4P thermal-magnetic curve D - In= 25A - Icn= 6kA - Vn= 400 Vac - 4 modules



FH84C32

BTDIN100 - 4P thermal-magnetic curve C - In= 32A - Icn= 10kA - Vn= 400 Vac - 4 modules



FV84C16

BTDIN250 - 4P thermal-magnetic curve C - In= 16A - Icu= 25kA - Vn= 400Vac - 4 modules



FN84B16

BTDIN60 - 4P thermal-magnetic curve B - In= 16A - Icn= 6kA - Vn= 400 Vac - 4 modules



FN84C32

BTDIN60 - 4P thermal-magnetic curve C - In= 32A - Icn= 6kA - Vn= 400 Vac - 4 modules



FA84C6

BTDIN45 - 4P thermal-magnetic curve C - In= 6A - Icn= 4,5kA - Vn= 400 Vac - 4 modules



FT84C20

BTDIN160 - 4P thermal-magnetic curve C - In= 20A - Icu= 16kA - Vn= 400 Vac - 4 modules



FH84D20

BTDIN100 - 4P thermal-magnetic curve D - In= 20A - Icn= 10kA - Vn= 400 Vac - 4 modules